

Фитинги Sanpress

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884


Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47


эл.почта: vag@nt-rt.ru || сайт: <https://viega.nt-rt.ru/>

TABLE OF CONTENTS

Pipes	150
Elbows	151
T-pieces	153
Adapters/elbows	154
Couplings	157
Reductions	158
Screw fittings	158
Caps, plugs	160
Flanges	160
Wall plates	161
Mounting units	162
Wall lead-ins	163
Smartloop inliner technology: internal circulation pipes	164
Compensators	165
Gunmetal shut-off valves, from 2017	165
Gunmetal ball valves, from 2017	166
Free-flow valves, from 2017	168
Accessories	
Tools	169
Sealing elements	169



PIPES



Sanpress Pipe 1.4521 (AISI 444)

- for potable water installation
- non-corroding steel
- laser welded


Model 2205

VdS	d	s	L [m]	LB	SB	PU	Article	DG
	12	1	6	✓		60	615 987	70
	15	1	6	✓		600	615 994	70
	18	1	6	✓		240	616 007	70
✓	22	1.2	6	✓		420	616 014	70
✓	28	1.2	6	✓		240	616 021	70
✓	35	1.5	6	✓		180	616 038	70
✓	42	1.5	6	✓		120	616 045	70
✓	54	1.5	6	✓		60	616 557	70
	15	1	6		✓	120	807 351	70
	18	1	6		✓	60	807 368	70
✓	22	1.2	6		✓	60	807 375	70
✓	28	1.2	6		✓	60	807 382	70
✓	35	1.5	6		✓	30	807 399	70
✓	42	1.5	6		✓	30	807 405	70
✓	54	1.5	6		✓	30	807 412	70

VdS = VdS certification

LB = large bundle

SB = small bundle



Sanpress XL Pipe 1.4521 (AISI 444)

- for potable water installation
- non-corroding steel
- laser welded

Model 2205XL

VdS	d	s	L [m]	LB	SB	PU	Article	DG
✓	76.1	2	6	✓		30	616 571	70
✓	88.9	2	6	✓		30	616 588	70
✓	108.0	2	6	✓		30	616 595	70
✓	76.1	2	6		✓	6	807 443	70
✓	88.9	2	6		✓	6	807 450	70
✓	108.0	2	6		✓	6	807 429	70

VdS = VdS certification

LB = large bundle

SB = small bundle


Sanpress Pipe
1.4401 (AISI 316)

- for potable water installation, gas installation
- non-corroding steel
- laser welded

Model 2203

d	s	L [m]	LB	SB	PU	Article	DG
12	1	6	✓		60	297 824	70
15	1	6	✓		600	102 036	70
18	1	6	✓		240	289 034	70
22	1.2	6	✓		420	102 708	70
28	1.2	6	✓		240	104 924	70
35	1.5	6	✓		180	108 588	70
42	1.5	6	✓		120	113 001	70
54	1.5	6	✓		60	193 676	70
15	1	6		✓	120	807 115	70
18	1	6		✓	60	807 122	70
22	1.2	6		✓	60	807 139	70
28	1.2	6		✓	60	807 146	70
35	1.5	6		✓	30	807 153	70
42	1.5	6		✓	30	807 160	70
54	1.5	6		✓	30	807 177	70

LB = large bundle

SB = small bundle


Sanpress XL Pipe
1.4401 (AISI 316)


- for potable water installation, gas installation
- non-corroding steel
- laser welded

Model 2203XL

d	s	L [m]	LB	SB	PU	Article	DG
76.1	2	6	✓		30	354 862	70
88.9	2	6	✓		30	354 855	70
108.0	2	6	✓		30	354 848	70
76.1	2	6		✓	6	807 207	70
88.9	2	6		✓	6	807 214	70
108.0	2	6		✓	6	807 184	70

LB = large bundle

SB = small bundle


ELBOWS

Sanpress Elbow 90°
with SC-Contur

- gunmetal or silicon bronze
- press connections

Model 2216

d	PU	Article	DG
12	5	298 340	76
15	5/100	103 750	76
18	5	281 267	76
22	5	104 818	76
28	5/50	106 348	76
35	5	111 953	76
42	1	119 560	76
54	1	199 395	76


Sanpress Elbow 90°
with SC-Contur

- gunmetal or silicon bronze
- press connection, plug-in end

Components

EPDM sealing element

Model 2216.1

d	PU	Article	DG
15	5	107 932	76
18	5	281 298	76
22	5	108 120	76
28	5	115 159	76
35	5	117 603	76
42	1	130 497	76
54	1	191 221	76



**Sanpress Elbow 45°
with SC-Contur**
- gunmetal or silicon bronze
- press connections
Components
EPDM sealing elements
Model 2226

d	PU	Article	DG	
15	5	113 186	76	
18	5	281 533	76	
22	5/50	112 004	76	
28	5	111 670	76	
35	5	116 156	76	
42	1	128 531	76	
54	1	197 506	76	



**Sanpress Elbow 45°
with SC-Contur**
- gunmetal or silicon bronze
- press connection, plug-in end
Components
EPDM sealing element
Model 2226.1

d	PU	Article	DG	
15	5	109 332	76	
18	5	281 564	76	
22	5	110 949	76	
28	5	113 346	76	
35	5	121 594	76	
42	1	134 471	76	
54	1	191 825	76	



Sanpress Crossover
- non-corroding steel
- plug-in ends
Model 2209.3

d	PU	Article	DG	
15	5	193 324	82	
18	5	289 010	82	
22	5	193 331	82	
28	5	193 294	82	

T-PIECES



Sanpress T-piece with SC-Contur
- gunmetal or silicon bronze
- press connections

Components
EPDM sealing elements
Model 2218

VdS	d1	d2	d3	PU	Article	DG
	12	15	12	5	313 630	76
	15	12	15	5	298 371	76
	15	15	15	5	106 614	76
	15	18	15	5	313 647	76
	15	22	15	5	298 388	76
	18	12	18	5	314 040	76
	18	15	15	5	281 397	76
	18	15	18	5	281 403	76
	18	18	18	5	281 410	76
	18	22	18	5	298 395	76
	22	12	22	5	314 071	76
	22	15	15	5	121 600	76
	22	15	18	5	298 432	76
	22	15	22	5	109 165	76
	22	18	18	5	298 401	76
	22	18	22	5	281 380	76
	22	22	15	5	298 418	76
	22	22	22	5/50	109 257	76
	22	28	22	5	313 623	76
	28	15	28	5	283 513	76
	28	18	22	5	314 101	76
	28	18	28	5	298 425	76
	28	22	22	5	135 102	76
	28	22	28	5	111 625	76
	28	28	15	5	314 132	87
	28	28	18	5	314 163	87
	28	28	28	5	111 915	76
	35	15	35	5	283 520	76
	35	18	35	5	313 616	76
	35	22	28	5	314 194	76
	35	22	35	5	113 469	76
	35	28	28	5	121 754	76
	35	28	35	5	118 341	76
	35	35	35	5	115 265	76
	42	15	42	1	314 224	87
	42	22	42	1	283 537	76
	42	28	42	1	283 544	76
✓	42	35	35	1	283 551	87
	42	35	42	1	120 672	76
	42	42	42	1	121 259	76
	54	22	54	1	195 991	76
	54	28	54	1	283 568	76
	54	35	54	1	197 469	76
✓	54	42	42	1	187 279	87
	54	42	54	1	198 541	76
	54	54	54	1	199 364	76


VdS = VdS certification



Sanpress T-piece with SC-Contur
- gunmetal or silicon bronze
- press connections, R-thread

Components
EPDM sealing elements
Model 2217.1

d1	R	d2	PU	Article	DG
22	¾	22	5	194 123	87
28	¾	28	5	194 130	87
35	¾	35	5	194 147	87
42	¾	42	1	273 231	87
54	¾	54	1	197 858	87
54	1	54	1	310 929	87
54	1¼	54	1	310 936	87




Sanpress T-piece with SC-Contur

- gunmetal or silicon bronze
- press connections, Rp-thread

Components

EPDM sealing elements, polygon

Model 2217.2

VdS	d1	Rp	d2	PU	Article	DG
	12	½	12	5	290 986	87
	15	¾	15	5	313 951	87
	15	½	15	5	115 630	87
	18	½	18	5	281 359	87
✓	22	½	22	5	115 944	87
✓	22	¾	22	5	313 975	87
✓	28	½	28	5	119 768	87
✓	28	¾	28	5	313 968	87
✓	35	½	35	5	121 945	87
✓	35	1	35	1	361 204	87
✓	42	½	42	1	126 230	87
✓	42	1	42	1	361 211	87
✓	54	½	54	1	197 353	87
✓	54	1	54	1	361 228	87

VdS = VdS certification


Sanpress T-piece G¼, with plug-in end with SC-Contur

- for extraction valve, drainage valve, sampling point for retrofitted installation in piping, connection of drainage valve with access to ball valve
- gunmetal or silicon bronze
- press connection, plug-in end, G-thread

Components

EPDM sealing element

Note

In piping that use Sanpress slip coupling model 2215.5.

Model 2217.4

d1	G	d2	PU	Article	DG
15	¼	15	1	705 596	87
18	¼	18	1	705 602	87
22	¼	22	1	705 619	87
28	¼	28	1	705 626	87
35	¼	35	1	705 633	87
42	¼	42	1	705 640	87
54	¼	54	1	705 855	87

ADAPTERS/ELBOWS

Sanpress Adapter with SC-Contur

- gunmetal or silicon bronze
- press connection, R-thread

Components

EPDM sealing element, polygon

Model 2211

VdS	d	R	PU	Article	DG
	12	¾	5	290 771	87
	12	½	5	290 764	87
	15	¾	5	297 985	87
	15	½	5/100	105 044	87
	15	¾	5	287 764	87
✓	22	½	5	297 961	87
✓	22	¾	5	104 306	87
✓	22	1	5	287 771	87
✓	28	¾	5	297 954	87
✓	28	1	5	106 508	87
✓	28	1¼	5	297 978	87
✓	35	1	5	297 947	87
✓	35	1¼	5	110 352	87
✓	35	1½	5	314 651	87
✓	42	1¼	5	297 930	87
✓	42	1½	1	115 340	87
✓	54	1½	1	314 668	87
✓	54	2	1	195 267	87

VdS = VdS certification


Sanpress Adapter with SC-Contur

- for connection screw fitting
- gunmetal or silicon bronze
- press connection, G-thread

Components

EPDM sealing element, polygon

Model 2211.4

d	G	PU	Article	DG
15	½	5	660 222	87


Sanpress Adapter with SC-Contur

- gunmetal or silicon bronze
- press connection, Rp-thread

Components

EPDM sealing element, polygon

Model 2212

VdS	d	Rp	PU	Article	DG
	12	¾	5	291 075	87
	12	½	5	291 068	87
	15	¾	5	298 074	87
	15	½	5	107 543	87
	15	¾	5	298 098	87
✓	22	½	5	298 067	87
✓	22	¾	5	108 465	87
✓	22	1	5	298 128	87
✓	28	½	5	428 174	87
✓	28	¾	5	298 081	87
✓	28	1	5	114 329	87
✓	28	1¼	5	298 104	87
✓	35	¾	5	357 542	87
✓	35	1	5	298 111	87
✓	35	1¼	5	116 774	87
✓	42	1¼	1	298 050	87
✓	42	1½	1	124 236	87
✓	54	1½	1	365 097	87
✓	54	2	1	195 304	87

VdS = VdS certification


Sanpress Adapter

- gunmetal or silicon bronze
- press connection, NPT male pipe thread

Components

EPDM sealing element, polygon

Model 2212.2

d	NPT	PU	Article	DG
15	½	5	493 912	87


Sanpress Adapter with SC-Contur

- gunmetal or silicon bronze
- press connection, Rp-thread

Components

EPDM sealing element, anti-twist protection

Model 2212.3

d	Rp	PU	Article	DG
15	½	5	287 016	87
18	½	5	298 913	87
22	½	5	287 009	87


Sanpress Adapter union with SC-Contur

- for steel pipe to Viega press connector systems
- gunmetal or silicon bronze
- compression fitting, press connection

Components

gasket, separator ring, clamping ring, union nut screw fitting, EPDM sealing element, polygon

Model 2215.6

DN	d	PU	Article	DG
25	28	1	588 564	87
32	35	1	588 328	87




Megapress Adapter with SC-Contur
potable water installation

- for steel pipes in accordance with EN 10220/10255 with galvanizing in accordance with EN 10240
- silicon bronze
- press connections

Components

EPDM sealing elements, cutting ring, separator ring

Model 4213.2

DN	D	d	PU	Article	DG
15	½	15	5	736 255	55
15	½	18	5	754 679	55
20	¾	22	5	736 279	55
25	1	28	5	736 293	55
32	1¼	35	1	736 309	55
40	1½	42	1	736 316	55
50	2	54	1	736 323	55


Sanpress Plug-in piece

- gunmetal or silicon bronze
- plug-in end, R-thread

Components

polygon

Model 2211.1

d	R	PU	Article	DG
12	½	5	291 310	87
15	½	5	115 418	87
18	½	5	285 081	87
18	¾	5	285 104	87
22	½	5	119 676	87
22	¾	5	116 767	87
28	1	5	122 034	87
35	1¼	5	125 288	87
42	1½	1	132 231	87


Sanpress Adapter

- press connection, NPT male pipe thread

Components

EPDM sealing element, polygon

Model 2211.2

d	NPT	PU	Article	DG
15	½	5	493 851	87
22	¾	5	493 868	87
28	1	5	493 875	87
35	1¼	5	493 882	87
42	1½	1	493 899	87
54	2	1	493 905	87


Sanpress Plug-in piece

- gunmetal or silicon bronze
- plug-in end, Rp-thread

Components

polygon

Model 2212.1

d	Rp	PU	Article	DG
12	½	5	291 341	87
15	½	5	117 733	87
18	½	5	287 085	87
18	¾	5	287 108	87
22	½	5	120 917	87
22	¾	5	117 481	87
28	¾	5	130 954	87
28	1	5	122 942	87
35	1	5	134 730	87
35	1¼	5	130 589	87
42	1½	1	135 430	87
54	2	1	199 104	87


Sanpress Plug-in elbow 90°

- gunmetal or silicon bronze
- plug-in end, Rp-thread

Model 2214.3

d	Rp	PU	Article	DG
15	½	5	308 001	87


Sanpress Adapter elbow 90° with SC-Contur

- gunmetal or silicon bronze
- press connection, R-thread

Components

EPDM sealing element, polygon

Model 2214

d	R	PU	Article	DG
12	¾	5	290 863	87
12	½	5	290 870	87
15	¾	5	314 361	87
15	½	5	112 950	87
15	¾	5	443 030	87
22	¾	5	115 623	87
28	1	5	118 730	87
35	1¼	5	127 329	87
42	1½	1	128 500	87
54	2	1	197 988	87

Sanpress with SC-Contur G3



Sanpress Adapter elbow 90° with SC-Contur

- gunmetal or silicon bronze
- press connection, R-thread

Components

EPDM sealing element

Model 2214.1

d	R	PU	Article	DG
15	1/2	5	335 281	87



Sanpress Adapter elbow 90° with SC-Contur

- gunmetal or silicon bronze
- press connection, Rp-thread

Components

EPDM sealing element

Model 2214.2

d	Rp	PU	Article	DG
12	3/8	5	290 924	87
12	1/2	5	290 931	87
15	3/8	5	298 241	87
15	1/2	5	108 441	87
15	3/4	5	314 385	87
22	1/2	5	298 234	87
22	3/4	5	283 711	87
22	1	5	314 378	87
28	1/2	5	442 033	87
28	3/4	5	446 611	87
28	1	5	283 728	87
35	1 1/4	5	283 704	87
42	1 1/2	1	299 415	87
54	2	1	299 422	87

COUPLINGS



Sanpress Coupling with SC-Contur

- gunmetal or silicon bronze
- press connections

Components

EPDM sealing elements

Model 2215

d	PU	Article	DG
12	5	308 636	76
15	5	107 727	76
18	5	282 660	76
22	5	108 090	76
28	5	108 618	76
35	5	114 930	76
42	1	116 835	76
54	1	215 835	76



Sanpress Slip coupling with SC-Contur

- gunmetal or silicon bronze
- press connections

Components

EPDM sealing elements

Model 2215.5

VdS	d	PU	Article	DG
	15	5	119 485	87
	18	5	287 061	87
✓	22	5	119 041	87
✓	28	5	122 133	87
✓	35	5	124 335	87
✓	42	1	131 494	87
✓	54	1	216 153	87

VdS = VdS certification



Sanpress Slip coupling with SC-Contur

- gunmetal or silicon bronze
- plug-in end, press connection

Components

EPDM sealing element

Model 2215.4

d	PU	Article	DG
22	5	588 533	87
28	5	588 540	87
35	5	588 557	87



REDUCTIONS



Sanpress Reducer with SC-Contur

- gunmetal or silicon bronze
- plug-in end, press connection

Components

EPDM sealing element

Model 2215.1

d1	d2	PU	Article	DG
15	12	5	298 302	76
18	12	5	287 344	76
18	15	5	287 375	76
22	12	5	366 865	76
22	15	5	108 250	76
22	18	5	287 337	76
28	15	5	288 228	76
28	18	5	298 319	76
28	22	5	109 974	76
35	22	5	115 753	76
35	28	5	116 934	76
42	22	5	287 368	76
42	28	1	124 489	76
42	35	1	122 775	76
54	22	5	287 351	76
54	28	1	194 239	76
54	35	1	194 222	76
54	42	1	198 879	76

SCREW FITTINGS



Sanpress Screw fitting with SC-Contur

- gunmetal or silicon bronze
- press connections
- flat sealing

Components

EPDM sealing elements, EPDM flat gasket, union nut screw fitting, polygon

Note

The union nut consists of brass.

Model 2260

d	PU	Article	DG
12	5	293 017	87
15	1	126 148	87
18	1	287 436	87
22	1	126 124	87
28	1	124 311	87
35	1	130 947	87
42	1	132 446	87
54	1	226 329	87



Sanpress Adapter union with SC-Contur

- gunmetal or silicon bronze
- press connection, Rp-thread
- flat sealing

Components

EPDM sealing element, EPDM flat gasket, union nut screw fitting, polygon

Note

The union nut consists of brass.

Model 2262

d	Rp	PU	Article	DG
12	1/2	5	293 024	87
15	1/2	1	131 937	87
15	3/4	1	133 160	87
18	1/2	1	283 384	87
18	3/4	1	314 910	87
22	3/4	1	125 318	87
22	1	1	133 900	87
28	3/4	1	365 103	87
28	1	1	128 975	87
35	1 1/4	1	138 875	87
42	1 1/2	1	141 745	87
54	2	1	222 017	87



Sanpress Adapter union with SC-Contur

- gunmetal or silicon bronze
- press connection, R-thread
- flat sealing

Components

EPDM sealing element, EPDM flat gasket, union nut screw fitting, polygon

Note

The union nut consists of brass.

Model 2265

d	R	PU	Article	DG
12	3/8	5	291 372	87
12	1/2	5	291 389	87
15	1/2	1	120 108	87
15	3/4	1	140 878	87
18	1/2	1	283 360	87
18	3/4	1	283 377	87
22	1/2	1	142 674	87
22	3/4	1	119 133	87
22	1	1	148 492	87
28	3/4	1	365 110	87
28	1	1	120 047	87
35	1 1/4	1	128 425	87
42	1 1/2	1	135 966	87
54	2	1	221 997	87


Sanpress Adapter union 90° with SC-Contur

- gunmetal or silicon bronze
- press connection, Rp-thread
- flat sealing, angled

Components

EPDM sealing element, EPDM flat gasket, union nut screw fitting, polygon

Note

The union nut consists of brass.

Model 2255

d	Rp	PU	Article	DG
12	1/2	5	292 980*	87
15	1/2	5	125 660	87
18	1/2	5	283 469	87
18	3/4	5	283 452	87
22	3/4	5	122 614	87
22	1	5	132 637	87
28	1	5	128 159	87
35	1 1/4	5	132 729	87
42	1 1/2	1	139 872	87
54	2	1	221 676	87

* = Discontinued, limited availability


Connection screw fitting with SC-Contur

- gunmetal or silicon bronze
- press connection, G-thread
- flat sealing

Components

EPDM sealing element, EPDM flat gasket, union nut screw fitting, polygon

Model 2263

VdS	d	G	PU	Article	DG
	12	3/8	1	475 956	87
	12	1/2	1	380 878	87
	12	3/4	1	293 611	87
	15	3/8	1	475 963	87
	15	1/2	1	380 885	87
	15	3/4	1	265 663	87
	15	1	1	305 000	87
	15	1 1/4	1	424 534	87
	22	3/4	1	351 502	87
✓	22	1	1	265 687	87
✓	22	1 1/4	1	367 015	87
✓	22	1 1/2	1	305 260	87
	28	1	1	692 629	87
✓	28	1 1/4	1	265 700	87
✓	28	1 1/2	1	305 048	87
✓	35	1 1/2	1	265 731	87
✓	35	2	1	305 024	87
✓	42	1 3/4	1	265 304	87
✓	42	2	1	305 031	87
✓	54	2 1/4	1	426 743	87
✓	54	2 3/8	1	265 328	87
✓	54	2 1/2	1	341 961	87
✓	54	2 3/4	1	426 750	87

VdS = VdS certification


Sanpress Connection screw fitting

- gunmetal or silicon bronze
- plug-in end, G-thread
- flat sealing

Components

EPDM flat gasket, union nut screw fitting, polygon

Note

The union nut consists of brass.

Model 2264

d	G	PU	Article	DG
15	3/4	1	338 503	87
18	3/4	1	338 510	87
22	1	1	338 527	87
28	1 1/4	1	338 534	87
35	1 1/2	1	338 541	87
42	1 3/4	1	338 558	87
54	2 3/8	1	338 565	87


Sanpress Insulating union with SC-Contur

- gunmetal or silicon bronze
- Rp-thread, press connection
- flat sealing

Components

EPDM sealing element, EPDM flat gasket, union nut screw fitting, separator ring, polygon

Note

The union nut consists of brass.

Model 2267

Rp	d	PU	Article	DG
1/2	15	1	469 450	87
3/4	15	1	469 467	87
1/2	18	1	469 474	87
3/4	18	1	469 481	87
3/4	22	1	469 498	87
1	22	1	469 504	87
1	28	1	469 511	87
1 1/4	35	1	469 528	87
1 1/2	42	1	469 535	87
2	54	1	469 542	87



CAPS, PLUGS



Pressure test plug

- for leakage test, temporarily closed piping section
- brass
- compression fitting, hose connection for filling hose

Components

KFE tap, union nut screw fitting

Model 2269

d	PU	Article	DG
15	1	141 523	87
18	1	289 423	87
22	1	140 557	87
28	1	142 568	87
35	1	144 111	87
42	1	144 999	87
54	1	187 798	87



Sealing element

EPDM

- suitable for pressure test plug model 2269

Model 2269.9

for d	internal-Ø	s	PU	Article	DG
35	32,15	3.2	5	754 150	87
42	38.5	3.7	5	754 167	87
54	51,2	4.13	5	754 174	87



Protective cap

- for pipe end
- not suitable for leakage and pressure test
- plastic

Model 2259.1

d	PU	Article	DG
15	10	611 149	76
18	10	612 054	76
22	10	612 061	76
28	10	612 078	76
35	10	612 085	76
42	10	612 092	76
54	10	612 108	76



Protective cap

- for pipe end
- not suitable for leakage and pressure test
- plastic

Model 2259.1XL

d	PU	Article	DG
76.1	10	612 122	76
88.9	10	612 139	76
108.0	10	612 146	76

FLANGES



Sanpress Flange adapter with SC-Contur

- gunmetal or silicon bronze
- flange adapter, press connection

Components

black powder-coated steel loose flange PN 10/16, EPDM sealing element, mounting bracket

Model 2259.5

DN	d	n	k [mm]	PU	Article	DG
25	28	4	85	1	479 855	87
32	35	4	100	1	479 879	87
40	42	4	110	1	479 886	87
50	54	4	125	1	479 893	87

n = number of holes
k = bolt circle diameter



Sanpress XL Flange PN 16

- gunmetal or silicon bronze
- Rp-thread

Model 2259.2XL

DN	Rp	PU	Article	DG
65	2½	1	641 597	88
80	3	1	641 603	88
100	4	1	641 610	88



Mounting set

- for flange connection
- galvanised steel

Components

4 screws, 8 washers, 4 nuts

Model 2259.7

DN	PN	M	L	PU	Article	DG
20/25	16	12	65	1	494 056	87
32/50	16	16	70	1	494 063	87

Sanpress with SC-Contur G3



Mounting set
- for flange connection
- galvanised steel
Model 2259.7XL

for DN	PN	M	L	PU	Article	DG
65/100	16	16	70	1	494 087¹	87
80/100	6	16	60	1	651 268²	87

¹⁾ with 8 screws, 16 washers and 8 nuts

²⁾ with 4 screws, 8 washers and 4 nuts



Gasket
- AFM 34/2
Model 2259.9

DN	PN	PU	Article	DG
25	16	10	409 128	87
32	16	10	409 135	87
40	16	10	409 142	87
50	16	10	409 258	87



Gasket
- AFM 34/2
Model 2259.9XL

DN	PN	PU	Article	DG
65	16	10	356 293	88
80	16	10	356 309	88
100	16	10	356 316	88

WALL PLATES



Sanpress Wall plate with SC-Contur
- gunmetal or silicon bronze
- press connection, Rp-thread
Components
EPDM sealing element, cuttable connection elbow, fixing flange
Model 2225

d	Rp	L	PU	Article	DG
15	½	45	5/25	116 552	87



Sanpress Wall plate with SC-Contur
- gunmetal or silicon bronze
- press connection, Rp-thread
Components
EPDM sealing element, fixing flange
Model 2225.5

d	Rp	PU	Article	DG
12	½	5	291 013	87
15	½	5/100	107 345	87
22	½	5	335 229	87
22	¾	5	116 057	87



Sanpress Wall plate with SC-Contur
- gunmetal or silicon bronze
- press connection, Rp-thread
Components
EPDM sealing element, spacer, fixing flange
Model 2225.6

d	Rp	PU	Article	DG
15	½	5	347 307	87




Sanpress Double wall plate with SC-Contur
- gunmetal or silicon bronze
- press connections, Rp-thread
Components
EPDM sealing elements, fixing flange
Model 2228.7

d1	Rp	d2	PU	Article	DG
15	½	15	1	687 892	87
18	½	18	1	692 797	87
22	½	22	1	687 908	87



Sanpress Wall plate T-piece with SC-Contur
- gunmetal or silicon bronze
- press connections, Rp-thread
Components
EPDM sealing elements, fixing flange
Model 2217.3

d1	Rp	d2	PU	Article	DG
15	½	15	1	644 864	87
22	½	22	1	625 726	87




Press-in nozzle


- for T-piece of Profipress, Sanpress, and Sanpress Inox systems with branch d15 in customised dimensioned supply lines
- gunmetal or silicon bronze
- plug-in end
- acc. to the Venturi principle

Note

For the water exchange in branched ring systems to rarely used draw-off points up to a length of 15 m (guide value).

Model 2211.5

d	PU	Article	DG
22	1	695 835	87
28	1	695 842	87
35	1	696 252	87
42	1	696 269	87
54	1	696 276	87
64	1	696 283	87


Pressure test plug

- for leakage test
- plastic
- G-thread
- hot water resistant

Components

gasket, metal thread insert

Model 1516.113

G	PU	Article	DG
$\frac{3}{8}$	10	116 644	24
$\frac{1}{2}$	10	100 766	24
$\frac{3}{4}$	10	107 666	24


Pressure test plug

- plastic
- G-thread

Components

gasket

Model 1516

G	PU	Article	DG
$\frac{3}{8}$	10	107 796	24
$\frac{1}{2}$	10/100	100 124	24
$\frac{3}{4}$	10	102 746	24

MOUNTING UNITS


Sanpress Mounting unit with SC-Contur

- press connections, Rp-threads
- long on one side

Components

EPDM sealing element, galvanised steel (flat) mounting bracket, long gunmetal or silicon bronze elbow (cuttable)

Model	d	Rp	L	DG	PU	Article	DG
2221	15	$\frac{1}{2}$	45	150/200	1	124 502	87
2221.1	15	$\frac{1}{2}$	45	80/100	1	135 119	87

DG = depth gauge


Sanpress Mounting unit with SC-Contur

- press connections, Rp-threads

Components

EPDM sealing element, short gunmetal or silicon bronze elbow, galvanised steel (offset) mounting bracket

Model 2222.6EX

d	Rp	DG	PU	Article	DG
12	$\frac{3}{8}$	120	1	357 351	87

DG = depth gauge


Sanpress Mounting unit with SC-Contur

- press connections, Rp-threads

Components

EPDM sealing element, short gunmetal or silicon bronze elbow, galvanised steel (flat) mounting bracket

Model 2222.05

d	Rp	DG	PU	Article	DG
15	½	150	1	308 681	87

DG = depth gauge


Sanpress Mounting unit with SC-Contur

- press connections, Rp-threads

Components

EPDM sealing element, short gunmetal or silicon bronze elbow, galvanised steel (flat) mounting bracket

Model 2222.2

d	Rp	DG	PU	Article	DG
15	½	100	1	308 674	87

DG = depth gauge


Mounting unit

- for Junkers gas combination boilers
- press connections, Rp-threads

Components

gas connection elbow with threaded connection – all other elbows with press connection, short gunmetal or silicon bronze elbow, EPDM sealing elements, leaking water connection, galvanised steel (offset) mounting bracket

Note

When gas connection Rp¾ or Rp1 is required, please replace the Rp½ elbow!

Model 2229

Rp	PU	Article	DG
½	1	309 398	87


Connection elbow 90°

- Rp-thread

Model 94477.0-713

Rp	PU	Article	DG
½	1	374 570¹	31
¾	1	489 298¹	31
1	1	138 066²	31

¹⁾ gunmetal

²⁾ brass


WALL LEAD-INS

Sanpress Wall lead-in with SC-Contur

- gunmetal or silicon bronze
- press connection, Rp-thread, G-thread
- angled

Components

EPDM sealing element

Model 2232.1

d	Rp	G	L	PU	Article	DG
15	½	¾	25	5	279 301	87
15	½	¾	35	5	279 318	87
15	½	¾	55	5	279 288	87
15	½	¾	65	5	279 295	87


Sanpress Wall lead-in with SC-Contur

- gunmetal or silicon bronze
- press connection, Rp-thread, G-thread

Components

EPDM sealing element

Model 2232.3

d	Rp	G	L	PU	Article	DG
15	½	¾	30	5	325 060	87



Anti-twist protection
- for wall lead-in
- galvanised steel
Model 2132

	PU	Article	DG	
	25	344 931	78	



Mounting set
- for wall lead-in
- G-thread
Model 1526.414-897

G	SS	PU	Article	DG	
¾	29	10	104 887	24	

SS = spanner size

SMARTLOOP INLINER TECHNOLOGY: INTERNAL CIRCULATION PIPES



Smartloop Connection set
- for hot water riser pipe with internal circulation pipe, hot water riser pipe from d28, circulation pipe d15
- gunmetal or silicon bronze
Components
plug, connection socket
Model 2276.1

d1	d2	d3	PU	Article	DG	
28	12	15	1	470 289	78	
35	12	15	1	470 272	78	
28/35	12	15	1	632 229	78	



Smartloop Pipe
- for internal circulation pipe
Model 2007.3

d	s	L [m]	PU	Article	DG	
12	1	75	75	650 032	78	



Smartloop Tension coupling
- for installation of the internal circulation pipe
Model 2276.9

for d	PU	Article	DG	
12	1	632 236	78	



Smartloop Coupling
- for repair of the internal circulation pipe
Model 2276.8

for d	PU	Article	DG	
12	1	643 188	78	



Pipe shear
- for Viega plastic pipe
Model 2040

for d	PU	Article	DG	
12-25	1	117 047	74	



Mounting pliers
Model 1077.2

for d	PU	Article	DG	
12-16	1	264 604	74	



Hand press tool
- for solid plastic pipe system, PB-system
Model 2782

for d	SI	PU	Article	DG	
12	12	1	401 436	74	

SI = for Smartloop


**Press jaw
PT2**
for plastic piping systems

- recommended for Pressgun 6 Plus, Pressgun 6, Pressgun 6 B, Pressgun 5, Pressgun 4B, Pressgun 4E, press machine PT3-H/EH, PT3-AH, press machine type 2 (PT2), Geberit/Mepla press machines type PWH 75, type N 230 V and type N rechargeable battery, Geberit/Mapress press machines type EFP II, ACO 1, ECO 1, ACO 201, AFP 201, EFP 201, ACO 202 and ECO 202, Ridgid press machines RP 10-S, RP 10-B, RP 330C/330B, RP 340
- phosphatised steel

Model 2799.7

F	SI	PU	Article	DG
12	12	1	425 302	74

F = for Fonterra

SI = for Smartloop


**Press jaw
Picco**
for plastic piping systems

- recommended for Pressgun Picco 6 Plus, Pressgun Picco 6, Pressgun Picco, battery-powered press machine Picco, Ridgid RP 210
- phosphatised steel

Model 2484.7

F	SI	PU	Article	DG
12	12	1	616 915	74

F = for Fonterra

SI = for Smartloop

COMPENSATORS

**Compensator
with SC-Contur**

- for expansion equalisation in cellar or riser pipe, storey connection pipe in heating and sanitary technology
- press connections

Components

EPDM sealing elements, gunmetal or silicon bronze press connector, stainless steel bellows

Model 2251

d	PU	Article	DG
15	1	690 250	87
18	1	690 267	87
22	1	690 274	87
28	1	690 281	87
35	1	690 298	87
42	1	690 304	87
54	1	690 311	87


GUNMETAL SHUT-OFF VALVES, FROM 2017

**Easytop Slanted seat valve
(free-flow valve)
with SC-Contur**

- press connections

Components

valve casing and top made of gunmetal or silicon bronze in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), stainless steel valve seat and valve plate unit, spindle transmission, position display open/closed, ergonomic handwheel and closed with medium marking green/red exchangeable, drain plug G $\frac{1}{4}$, EPDM sealing elements

Technical data

operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 90 °C

with DVGW-test mark

Model 2237.5

DN	d	PU	Article	DG
15	15	5	756 864	95
15	18	5	756 871	95
20	22	5	756 888	95
25	28	5	756 895	95
32	35	1	756 901	95
40	42	1	756 918	95
50	54	1	756 925	95



**Easytop KRV slanted seat valve
(combined free-flow valve with
backflow preventer)
with SC-Contur**

- press connections

Components

valve casing and top made of gunmetal or silicon bronze in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), stainless steel valve seat and valve plate unit, spindle transmission, position display open/closed, ergonomic handwheel and closed with medium marking green/red exchangeable, test connection, drain plug G $\frac{1}{4}$, EPDM sealing elements

Technical data

operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 90 °C

with DVGW-test mark

Model 2238.5

DN	d	PU	Article	DG
15	15	5	757 199	95
15	18	5	757 205	95
20	22	5	757 212	95
25	28	5	757 229	95
32	35	1	757 236	95
40	42	1	757 243	95
50	54	1	757 250	95



**Easytop Backflow preventer
with SC-Contur**

- press connections

Components

valve casing and top made of gunmetal or silicon bronze in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), stainless steel valve seat and valve plate unit, test connection, drain plug G $\frac{1}{4}$, EPDM sealing elements

Technical data

operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 90 °C

with DVGW-test mark

Model 2239.4

DN	d	PU	Article	DG
15	15	5	757 526	95
15	18	5	757 533	95
20	22	5	757 540	95
25	28	5	757 557	95
32	35	1	757 564	95
40	42	1	757 571	95
50	54	1	757 588	95

GUNMETAL BALL VALVES, FROM 2017



**Easytop Ball valve
with SC-Contur**

- press connections

- Full Port

Components

silicon bronze valve casing in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), maintenance-free selector shaft (Viega recommends to open and close the ball valve completely every six months), actuating lever T-form with medium marking green/red exchangeable, stainless steel ball, EPDM sealing elements (press connections)

Technical data

operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 110 °C

with DVGW-test mark

Model 2275

DN	d	PU	Article	DG
15	15	1	746 377	95
15	18	1	746 384	95
20	22	1	746 391	95
25	28	1	746 407	95
32	35	1	746 414	95
40	42	1	746 421	95
50	54	1	746 438	95



Easytop Ball valve with SC-Contur

- not suitable for Easytop insulating shell model 2275.90
- silicon bronze
- press connections
- Full Port

Components

silicon bronze valve casing in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), maintenance-free selector shaft (Viega recommends to open and close the ball valve completely every six months), actuating lever L shape, stainless steel ball, EPDM sealing elements (press connections)

Technical data

operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 110 °C

with DVGW-test mark

Model 2275.10

DN	d	PU	Article	DG
15	15	1	774 851	95
15	18	1	774 868	95
20	22	1	774 875	95
25	28	1	774 882	95
32	35	1	774 899	95
40	42	1	774 905	95
50	54	1	774 912	95



Easytop Ball valve with SC-Contur

- press connections
- Full Port

Components

silicon bronze valve casing in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), maintenance-free selector shaft (Viega recommends to open and close the ball valve completely every six months), actuating lever T-form with medium marking green/red exchangeable, stainless steel ball, EPDM sealing elements (press connections), drain plugs G $\frac{1}{4}$ on both sides with draining valve G $\frac{1}{4}$

Technical data


operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 110 °C

with DVGW-test mark

Model 2275.3

DN	d	PU	Article	DG
15	15	1	746 681	95
15	18	1	746 698	95
20	22	1	746 704	95
25	28	1	746 711	95
32	35	1	746 728	95
40	42	1	746 735	95
50	54	1	746 742	95



Easytop Ball valve with SC-Contur

- press connection, Rp-threads
- Full Port

Components

silicon bronze valve casing in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), maintenance-free selector shaft (Viega recommends to open and close the ball valve completely every six months), stainless steel ball, actuating lever T-form with medium marking green/red exchangeable, EPDM sealing element (press connection), polygon

Technical data

operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 110 °C

with DVGW-test mark

Model 2275.4

DN	d	Rp	PU	Article	DG
15	15	$\frac{1}{2}$	1	746 759	95
15	18	$\frac{1}{2}$	1	746 766	95
20	22	$\frac{3}{4}$	1	746 773	95
25	28	1	1	746 780	95
32	35	$1\frac{1}{4}$	1	746 797	95
40	42	$1\frac{1}{2}$	1	746 803	95
50	54	2	1	746 810	95

FREE-FLOW VALVES, FROM 2017



Easytop Free-flow valve with SC-Contur

- press connections

Components

gunmetal or silicon bronze valve casing in accordance with DIN EN 1982 and metal evaluation criteria (UBA) (German Federal Environmental Agency), plastic turning handle, EPDM sealing elements (press connections)

Technical data

operating pressure max. 1.6 MPa (PN 16)

operating temperature max. 90 °C
with DVGW-test mark

Model 2278

d	PU	Article	DG	
15	1	747 312	95	
18	1	747 329	95	
22	1	747 336	95	

ACCESSORIES TOOLS



Deburrer

- for internal or external deburring, copper pipe, stainless steel pipe, Prestabo pipe
- steel

Model 2292.2

for d	PU	Article	DG
12–54	1	343 019	74



Deburrer

- for internal or external deburring, copper pipe, stainless steel pipe, Prestabo pipe
- steel

Model 2292.4XL

for d	PU	Article	DG
64.0–108.0	1	556 310	74



Cutting wheel

- steel

Components

bolt, safety ring

Model	PRi	PRe	PU	Article	DG
2291.1	✓		1	140 410	74
2291.2		✓	1	312 497	74

PRi = to the pipe cutter (Ridgid) (grey)

PRe = to the pipe cutter (Rems) (yellow)



Insertion depth template

- for marking the insertion depth of metallic pipes

Model 2494

for d	PU	Article	DG
12–54	1	625 085	74



Marking pen

- for Viega press connector systems

Model 2490.1

	PU	Article	DG
	1	606 121	74

ACCESSORIES SEALING ELEMENTS



Sealing element

FKM

- for areas of application with high temperatures e.g. district heat supply systems up to 140 °C and 1.6 MPa, low-pressure steam systems ≤ 120 °C and < 0.1 MPa, solar installations/vacuum pipes

Note


The Prestabo system is not suitable for low-pressure steam systems!

Use in any other area of application requires consultation with our Technical Consulting!

Model 2286

VdS	for d	internal-Ø	s	PU	Article	DG
	12	12.1	2.35	5	459 376	87
	15	15.1	2.6	5	459 390	87
	18	18.2	2.6	5	459 406	87
✓	22	22.2	3.1	5	459 413	87
✓	28	28.3	3.1	5	459 420	87
✓	35	35.4	3.25	5	459 437	87
✓	42	42.4	4.13	5	459 444	87
✓	54	54.4	4.13	1	459 451	87

VdS = VdS certification





Sealing element FKM

- for areas of application with high temperatures e.g. district heat supply systems up to 140 °C and 1.6 MPa, low-pressure steam systems ≤ 120 °C and < 0.1 MPa, solar installations/vacuum pipes, Sanpress XL

Note

Use in any other area of application requires consultation with our Technical Consulting!

Model 2286XL

for d	internal-Ø	s	PU	Article	DG	
76.1	77	5	1	459 468	88	
88.9	90	5	1	459 475	88	
108.0	109	5	1	459 482	88	



Sealing element EPDM

- for potable water installation, heating installation
- temperature resistant to 110 °C

Model 2289

VdS	for d	internal-Ø	s	PU	Article	DG	
	15	15.1	2.6	10	183 400	87	
	18	18.2	2.6	10	281 595	87	
✓	22	22.2	3.1	10	183 523	87	
✓	28	28.3	3.1	10	184 452	87	
✓	35	35.4	3.25	10	181 208	87	
✓	42	42.4	4.13	10	184 940	87	
✓	54	54.4	4.13	10	191 153	87	

VdS = VdS certification



Sealing element EPDM

- for Sanpress XL, potable water installation, heating installation
- temperature resistant to 110 °C

Model 2289XL

for d	internal-Ø	s	PU	Article	DG	
76.1	77	5	10	364 816	88	
88.9	90	5	10	364 823	88	
108.0	109	5	10	364 830	88	

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: vag@nt-rt.ru || сайт: <https://viega.nt-rt.ru/>